

SOROZAT	TÍPUS	ÉRZÉKELŐ	OBJEKTÍV	LÁTÓSZÖG/ NAGYÍTÁS	ÉSZLELÉSI TÁVOLSÁG (1,7 m × 0,5m objektum esetén)	
BUDGIE  Kis méret	BC06	160×120, 17 μm	6,2 mm	24,7°	1×	250 m
	BE07	256×192, 12 μm	6,9 mm	25°	1×	326 m
LYNX  Kis méret	LC06	160×120, 17 μm	6,2 mm	24,7°	1×	250 m
LYNX Pro  Kis méret Kézi Élességállítás	LE10	256×192, 12 μm	10 mm	24,7°	1×	500 m
	LE15	256×192, 12 μm	15 mm	11,7°	1×	750 m
	LH15	384×288, 12 μm	15 mm	17,5°	1,47×	750 m
	LH19	384×288, 12 μm	19 mm	13,8°	1,86×	900 m
	LH25	384×288, 12 μm	25 mm	10,5°	2,45×	1200 m
OWL  OLED Kijelző Kézi Élességállítás	OH25	384×288, 17 μm	25 mm	14,88°	1,5×	900 m
	OH35	384×288, 17 μm	35 mm	10,66°	2,14×	1300 m
	OQ35	640×512, 17 μm	35 mm	17,7°	1,4×	1300 m
FALCON  Képjavitó Eljárás 20 mK Érzékenység	FH25	384×288, 12 μm	25 mm	10,5°	2,17×	1200 m
	FH35	384×288, 12 μm	35 mm	7,53°	3,03×	1800 m
	FQ35	640×512, 12 μm	35 mm	12,54°	1,82×	1800 m
	FQ50	640×512, 12 μm	50 mm	8,75°	2,6×	2600 m

HŐKAMERA, ÉJJELLÁTÓ



SOROZAT	TÍPUS	ÉRZÉKELŐ	OBJEKTÍV	LÁTÓSZÖG/ NAGYÍTÁS	ÉSZLELÉSI TÁVOLSÁG (1,7 m × 0,5m objektum esetén)
GRYPHON Fúziós Megjelenítés 	GH25	384×288, 12 μm	25 mm	10,53° 2,4×	1200 m 
	GH35	384×288, 12 μm	35 mm	7,5° 3,4×	1800 m 
	GQ35	640×512, 12 μm	35 mm	11° 2×	1800 m 
GRYPHON Fúziós Megjelenítés Lézeres Táv mérő 	GH25L	384×288, 12 μm	25 mm	10,53° 2,4×	1200 m 
	GH35L	384×288, 12 μm	35 mm	7,5° 3,4×	1800 m 
	GQ35L	640×512, 12 μm	35 mm	11° 2×	1800 m 
	GQ50L	640×512, 12 μm	50 mm	8,8° 2,9×	2600 m 

Kétszemeres betekintésű hőkamera

RAPTOR ^{ÚJ!}  20 mK Érzékenység Fúziós Megjelenítés	RH50L	384×288, 12 μm	50 mm	5,3° 5,7×	2600 m 
	RH50LN	384×288, 12 μm	50 mm	5,3° 5,7×	2600 m 
	RQ50L	640×512, 12 μm	50 mm	8,8° 3,4×	2600 m 
	RQ50LN	640×512, 12 μm	50 mm	8,8° 3,4×	2600 m 
RAPTOR ^{ÚJ!}  Lézeres távmérő 1000 m-ig	TS56-RQ50L	640×512, 12 μm	50 mm	8,8° 3,4×	2600 m 
	TS56-RG75L	640×512, 12 μm	75 mm	5,9° 5,1×	3600 m 

Éjjellátó kamera, beépítet infravetővel

HEIMDAL ^{ÚJ!}  Kézi Élességállítás AMOLED Kijelző	H4D	2560×1440	31 mm	13,66° 1×	200 m 
--	-----	-----------	-------	-----------	---