

## Quantec-Pro Cardiac Call Point

Part No. **QP902CP**



### Overview

- A stylish surface-mounting Quantec-Pro cardiac call point.
- Specifically designed to generate cardiac calls on a Quantec-Pro call system when its blue pull-to-activate call switch is activated,
- Switch activation causes a distinct tone to sound throughout the facility accompanied by blue flashing lights (as programmed).
- If overdoor lights are required outside the room in which the QP902CP is located, use a QP906 tri-colour overdoor light or a QP906A tri-colour addressable overdoor light with sounder.



### More Information

Quantec-Pro is C-TEC's next generation addressable call system. It keeps everything that is good about existing Quantec – stable protocol, ease of system set-up, optional Cloud based data monitoring – and enhances it with stylish devices, improved power efficiency, greater programming flexibility and more. The result – a powerful, aesthetically-pleasing call system that is perfect for use across the entire care sector.

### Technical Specifications

Power requirements	Nominal 24V DC (from Quantec Controller/Network)
Quiescent current	0.7mA.
Alarm current	15mA.
Indicators	Red/green/blue confidence LED.
Controls	Blue activation pull switch (non-latching).
Connections	CONN2 (NET-; NET+; R/B; G; SW).



Expansion connections	R/B; G; SW terminals allow the connection of optional dummy/extender OD lights, dummy/extender call points & dummy/extender ceiling pulls.
Onboard Sounder	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	120 W x 100 H x 58 D mm (including activation pull switch). Surface mounting.
Construction & finish	Polycarbonate RAL9003.
IP Rating	IP21.
Weight	110g.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom