

Quantec Infrared Ceiling Receiver Extender

Part No. **QT302RXS**



Overview

- Connects to an addressable Quantec infrared receiving device to increase IR coverage.
- Accepts infrared calls from compatible Quantec staff attack transmitters, patient neck/wrist pendants and staff attendance pendants.
- Typically used in bedrooms, corridors, common rooms and any other area requiring extended infrared coverage.
- Typical 10m line of sight receiving range.
- Up to three extenders can be used per addressable receiving device.



More Information

Technical Specifications

Quiescent current	Less than 2mA.
Indicators	n/a.
Controls	n/a.
Connections	+V; -V; IR. Wire as a dummy/extender to a Quantec Addressable Call Point or Infrared Ceiling Receiver. See instructions for details.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Sounder	No,
Onboard Infrared Receiver	Yes - will accept calls from compatible Quantec infrared transmitters.
Product dimensions (mm)	87 W x 87 H x 23 D mm. Can be mounted on a standard UK 25mm single gang flush or surface back box.



Construction & finish	Plastic.
IP Rating	IP40.
Weight	60g
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom