

Infrared Patient Neck Pendant (push for call)

Part No. **QT432**



Overview

- Allows patients in bedrooms and communal areas to remotely trigger standard calls via a Quantec infrared call point, ceiling receiver or radio receiver
- Alleviates the need for long, potentially hazardous tail call leads.
- Supplied with an anti-ligature neck lanyard.
- 10m line-of-sight IR transmitting range.
- Radio coverage dependent on the Quantec receiving device used.
- Powered by a user-replaceable 12V alkaline battery.
- Can be programmed with a unique User ID so staff can see who is calling using a QT423 configurator.
- Supplied with a sheet of coloured markable labels.



More Information

Technical Specifications

Compatibility	Compatible with C-TEC's Quantec call systems.
Type	Infrared/Radio.
Coverage	10m line-of-sight infrared coverage (940nm modulated @ 38 Khz); 60m typical radio coverage dependent on environmental factors (RF868.3 MHz).
Max battery size and type	12 Volt Type A23/23A (8LR50) alkaline (non-rechargeable). User replaceable.



Indicators	Confidence LED/battery status indicator.
Controls	1 x activation button (triggers a Standard call).
Product dimensions (mm)	47 W x 83 H x 16 D mm.
Construction & finish	TBC.
IP Rating	IP41.
Weight	30g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Notes	The transmitter's operation can be tailored to suit a specific site using a QT423 Configurator. Refer to the device's instructions for details.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom