

Infrared Patient Wrist Pendant (push for call)

Part No. OT432W



Overview

- Allows patients in bedrooms and communal areas to remotely trigger standard calls via a Quantec infrared call point, ceiling receiver or radio receiver
- Supplied on an adjustable wrist strap alleviating the need for long and potentially hazardous tail call leads.
- 10m line-of-sight IR transmitting range.
- Radio coverage dependent on the Quantec receiving device used.
- Powered by a user-replaceable 12V alkaline battery.
- Can be programmed with a unique User ID so staff can see who is calling using a QT423 configurator.
- Supplied with a sheet of coloured markable labels.



More Information

Technical Specifications

Compatibility Compatible with C-TEC's Quantec call systems.

Type Infrared/Radio.

10m line-of-sight infrared coverage (940nm modulated @ 38 Khz); 60m typical radio coverage dependent Coverage

on environmental factors (RF868.3 MHz).

Max battery size and type $12\ Volt\ Type\ A23/23A\ (8LR50)$ alkaline (non-rechargeable). User replaceable.

Indicators Confidence LED/battery status indicator. Controls 1 x activation button (triggers a Standard call).



T 01942 322744

E sales@c-tec.co.uk



















Product dimensions (mm) 47 W x 83 H x 16 D mm.

Construction & finish TBC. IP Rating IP41. Weight 30g.

Operating conditions/temperature -5° C to $+40^{\circ}$ C. Max. relative humidity 95% non-condensing.

The transmitter's operation can be tailored to suit a specific site using a QT423 Configurator. Refer to the Notes

device's instructions for details.















