

Overdoor Light

Part No. QT606



Overview

- Provides visual indication of calls made from a Quantec call point outside bedrooms, WCs, etc.
- Flash and colour sequence changes/intensifies to reflect the urgency of the incoming call.
- Dual red and green LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Finished in tough, durable ABS plastic.
- Overdoor lights with sounders and addressable overdoor lights and sounders (to provide area indication at corridor junctions etc.) are also available.



More Information

Technical Specifications

Quiescent current	0mA (none).
Alarm current	40mA.
Indicators	Dual ultra-bright red and green Alarm LEDs (Flash rate and colour sequence changes/intensifies to reflect the urgency of the incoming call).
Connections	R (Red); G (Green); Net +; Net -. Wire as a dummy/extender to a Quantec Addressable Call Point or Accessible Toilet Reset Point. See instructions for details.
Onboard Sounder	No,



Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	48g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom