



SPP-C08020E

M12-RJ45 Ethernet cable 2M (6.6ft)



C€ ENI





Key features

Color: Blue

Material: PVC/PE

• Protect against dust, moisture and vibration

• Length : 2M (6.6ft)

Compatible Accessories (Optional)







TNS-9040IBC

TNS-9050IBC

TNS-9060IBC



SPP-C08020E

M12-RJ45 Ethernet cable 2M (6.6ft)



Specifications

CONNECTIONS	
Type	CAT6, X-coded
Camera End	M12, Male
System End	RJ45 , MT 8P8C MALE
Contact Plating	Gold
Connector Type	M12 8PIN X-CODE
Wiring Configuration	EIA/TIA 568B
PHYSICAL	
Cable Jacket Color	Blue
Cable Jacket Matereial	PVC/PE
Cable Jacket Rating	CMR-LP
Cable Shielding	S/D1; al 125% coverage, s/d2: braid 65%~70% coverage
Cable Outer Diameter	6.5mm
Number of Conductors	4 Pair
Conductor Material	Bare copper 4*2*7*0.20mm
Conductor Gauge	AWG24
Wire Gauge (AWG)	4*2*7*0.20mm cat6 S/FTP
Cable Length	2M(6.6ft)
ENVIRONMENTAL	
Operating Temperature Range	-10° to 50°C
Storage Temperature Range	−20° to 70°C
Operating Humidity Range	0% to 90% RH, Non–Condensing
Storage Humidity Range	0% to 90% RH, Non–Condensing
Power Provided to Connected Device	51W (60W @ SOURCE, 51W @ DEVICE)
COMMUNICATIONS	
Bandwidth per TIA Standard	250Mhz
Maximum Bandwidth as Tested	500Mhz
Network Compatibility	1 Gbps
IEEE Standards Supported	802.3bt
FEATURES & SPECIFICATIONS	
IP68 Rated	yes
Snagless Connector	yes
STANDARDS & COMPLIANCE	
Protection Rating	IP68
Product Certifications	UL Listed:
Product Compliance	CE, RoHS, IEEE 802.3bt PoE++, REACH, UKCA, Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period	Lifetime limited warranty



SPP-C08020E

M12-RJ45 Ethernet cable 2M (6.6ft)



